## Air Fly Pro

**Core Product** 

SKAARHOJ Air Fly Pro - Universal Live Switching Controller with PTZ section

SKAARHOJ's most popular live switching controller features a 12-channel program/preview row with dedicated silicon buttons, an advanced transition section, and freely assignable buttons that can be used for macros, aux busses, and navigating menus. Air Fly Pro features a unique PTZ section with an elastomer joystick and zoom rocker, enabling you to adjust any SKAARHOJ-supported PTZ camera position or setting. Its compact and durable design makes it an ideal choice for both studio and mobile broadcast setups, ensuring seamless integration and superior control across various devices and platforms, including the most popular BlackMagic ATEM, vMix, and Tricaster.



## **Benefits**

- Hall Effect T-bar for smooth, precise transitions and a classic ME section for familiarity and ease of use.
- Blue Pill Inside consolidates control into a single unit for a streamlined setup and cost efficiency.
- New proprietary T-bar and full-height display offer an upgraded user interface and enhanced visual monitoring.
- Eliminates the need for separate Blue Pill hardware, reducing complexity without sacrificing functionality.
- Designed for those who value an all-in-one control solution, ensuring a tidy and efficient workspace.
- Integrates PTZ and Live Switching into one seamless controller, perfect for solo operators.

## **Features**

- Extensive list of supported devices
- Advanced ergonomics
- Versatile connectivity via IP
- Durable build quality
- Designed with modularity in mind
- 12 program and 12 preview buttons
- 12 AUX/sends/macro silicone buttons
- 12 miscellaneous buttons
- SKAARHOJ unique T-bar with LED ring
- 4 assignable transition/quick-shot buttons
- 4 dedicated transition
- 2 user buttons
- PTZ section with elastomer joystick and zoom rocker with 2 backlit encoders
- Multiple OLED display for labels and feedback
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested adopted by professionals worldwide



Hardware Specifications	
Component Highlights	SKAARHOJ Hall Effect T-Bar with OLED display and LED ring
Buttons	Elastomer Four-Way Button (x18); Elastomer Four-Way Button w/Display (x40)
Encoders	Encoder (x2)
Analog Components	T-bar w/RGB (x1); Elastomer Zoom Rocker (x1); Elastomer Joystick, Left-Right (x1); Elastomer Joystick, Up-Down (x1)
Programmable OLED Tiles	64x32 pixels (x28); 64x32 pixels, gray (x12); 256x32 pixels, gray (x1); 112x32 pixels (x5)
Other	LED-Bar, 3 steps (x18); OLED Display Tile (x2)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive
	PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Peripherals	USB-A 2.0 (500 mA) for Stream Deck, X-keys, additional networking adapters, frame grabbers etc.
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	1878 g
Shipping Box Weight	2494 g
In The Box	(This Product)
	12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002550

## **Technical Drawings**



