Inline 10

Built To Order

SKAARHOJ Inline 10 – Universal Compact Desktop Controller

Inline 10 is a compact utility controller featuring 4 encoders and 6 Four-way buttons, making it exceptionally suitable for simple color grading of cameras or adjusting settings on various devices. Its compatibility with Raw Panel protocol enables custom integrations, offering a versatile tool for production environments. Whether for live events, studio productions, or on-location shoots, Inline 10 provides precise control in a highly portable package. Its intuitive design ensures quick adjustments, enhancing the creative workflow and ensuring optimal results across various applications.



Benefits

- Compact design suitable for various production environments
- Enables precise color grading and setting adjustments
- Supports Raw Panel protocol for custom integrations
- Highly portable for on-location shoots and studio productions
- Intuitive control layout for quick and effective adjustments

Features

- Extensive list of supported devices
- Versatile connectivity via IP
- · Durable build quality
- 6 4-way programmable buttons
- 4 backlit encoders
- OLED displays for labels and feedback
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested adopted by professionals worldwide



Hardware Specifications	
Buttons	Elastomer Four-Way Button w/Display (x6)
Encoders	Encoder (x4)
Programmable OLED Tiles	64x32 pixels (x6); 112x32 pixels (x4)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive
	PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	332 g
Shipping Box Weight	786 g
In The Box	(This Product)
	12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive
	Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002987

Technical Drawings

