Live Fly w/NKK Buttons

Built To Order

SKAARHOJ Live Fly – Universal Compact Switching Controller with NKK buttons

Building on the foundation of the Live Fly, this version upgrades the experience with high-quality Japanese NKK buttons featuring sculptured caps for professional operation and style. It includes all functionalities of the Live Fly, such as 9 buttons for input selection, a utility row with OLED displays, two encoders, dedicated Cut and Auto buttons, and more, designed to enhance control and flexibility in live production settings. The addition of NKK buttons ensures a tactile, reliable response for fast-paced environments, making it an essential tool for broadcast professionals seeking precision and durability.



Benefits

- Features high-quality Japanese NKK buttons for professional use
- Sculptured caps enhance tactile response and operational style
- Includes all functionalities of the Live Fly with upgraded controls
- Ideal for fast-paced live production and broadcast environments
- Ensures precision and durability for reliable, long-term use

Features

- Extensive list of supported devices
- Versatile connectivity via IP
- Durable build quality
- 9 program / preview NKK buttons
- AUX/sends/macro section
- Dedicated transition section with fader
- 2 user buttons
- Multiple OLED display for labels and feedback
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested adopted by professionals worldwide



Hardware Specifications	
Component Highlights	Sculptured cap NKK broadcast buttons
Buttons	Sculptured Hard Cap Button w/display (x9); Elastomer Four-Way Button w/Display (x6); Sculptured Hard Cap Button (x2); Elastomer Four-Way Button (x4)
Encoders	Encoder (x2)
Analog Components	Slider 45mm (x1)
Programmable OLED Tiles	64x32 pixels (x15); 112x32 pixels (x4)
Other	LED-Bar, 3 steps (x6); LED-Bar, 10 steps (x1)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive
	PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	634 g
Shipping Box Weight	1104 g
In The Box	(This Product)
	12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive
	Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002857

Technical Drawings



