# Live Fly

#### **Built To Order**

### SKAARHOJ Live Fly – Universal Compact Switching Controller

Live Fly is a compact switching surface tailored for ATEM, vMix, Tricaster, and more, featuring 9 buttons for input selection and a utility row of 6 buttons with OLED displays for dynamic configuration. This highly adaptable controller includes a shift key for accessing up to 18 sources, two encoders for precise settings adjustment, dedicated Cut and Auto buttons, a Fade-To-Black button, and two user keys. Its flexibility and intuitive design make it a cornerstone for live production, offering streamlined operations and enhancing workflow efficiency.



## **Benefits**

- Tailored for multiple platforms including ATEM, vMix, Tricaster
- 9 input selection buttons and a shift key for extended control
- OLED displays for dynamic, customizable configurations
- Two encoders for precise adjustment of settings
- Enhances workflow efficiency in live production environments


#### **Features**


- Extensive list of supported devices
- Versatile connectivity via IP
- Durable build quality
- 9 program / preview buttons
- AUX/sends/macro section
- Dedicated transition section with fader
- 2 user buttons
- Multiple OLED display for labels and feedback
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested adopted by professionals worldwide



Hardware Specifications	
Buttons	Elastomer Four-Way Button w/Display (x15); Elastomer Four-Way Button (x6)
Encoders	Encoder (x2)
Analog Components	Slider 45mm (x1)
Programmable OLED Tiles	64x32 pixels (x15); 112x32 pixels (x4)
Other	LED-Bar, 3 steps (x6); LED-Bar, 10 steps (x1)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	592 g
Shipping Box Weight	1006 g
In The Box	(This Product)
	12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002864

# **Technical Drawings**





278 mm 11"

