

RCP Pro

Core Product

SKAARHOJ RCP Pro - Universal Camera Shading Panel

RCP Pro er SKAARHOJ's højdepunkt af kameraskyggecontrollere, der integrerer et nyt joystick med en indbygget Tally Light og OLED-skærm til dynamisk at vise irisværdier. Den kan prale af en stor, vinklet skærm for optimal synlighed, kombineret med et væld af fuldt tilpasselige knapper og knapper til uovertruffen kontrol. RCP Pro, der løfter sig fra standard RCPv2, tilbyder en luksuriøs oplevelse med Blue Pill Inside, hvilket sikrer kompatibilitet med nutidens avancerede kameraer som RED, Canon, ARRI og Panasonic Lumix. Blue Pill Inside, SKAARHOJ's banebrydende platform, forbedrer kontrolmulighederne, som beskrevet i SKAARHOJ's informative YouTube-video.



Fordele

- Moderne design, ideel til nybyggede eller renoverede OB-lastbiler.
- Bevarer fuld kontrolfunktionalitet med et proprietært RCP-håndtag og OLED-skærm.
- Kompatibel med en lang række kameraer via Reactor og Blue Pill-kerner.
- Dedikerede OLED-skærme til hver indkoder giver klar, øjeblikkelig feedback.
- Understøtter standard og eksklusive TriClass-konfigurationer til skræddersyet styring.
- Maksimerer begrænsede pladser med dets effektive design og alsidige kontrolmuligheder.
- Tilbyder førsteklasses kameraskyggefunktioner.

Funktioner

- Unique Joystick for iris adjustments and black level pedestal
- 8 buttons for camera selection and presets
- 8 encoders for shading and menu cycling
- Crisp display for monitoring of values
- Joystick pad for adjusting PTZ cameras
- Four-way buttons for shortcuts and camera settings
- Universal control of multiple 3rd party devices
- Industry-standard form factor
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark

Hardware Specifications	
Component Highlights	SKAARHOJ exclusive fader handle with display, LED, pedestal ring and push function ('Sony feel') Raised Display
Buttons	Elastomer Button (x13); Elastomer Four-Way Button w/Display (x8); Elastomer Four-Way Button (x1); Joystick top button (x1)
Encoders	Encoder w/LED ring (x8); Encoder (x1); Joystick encoder (x1)
Analog Components	Elastomer Joystick, Left-Right (x1); Elastomer Joystick, Up-Down (x1); Joystick fader (x1); Opto-isolated Input (to GND) (x1)
Programmable OLED Tiles	128x32 pixels (x1); 128x64 pixels (x1); 64x64 pixels (x2); 64x32 pixels, gray (x14); 64x32 pixels (x12)
GPIOs	Opto-isolated Input (to GND) (x3)
Other	LED-Bar, 10 steps (x1); Relay Output (to GND) (x3); LED (x1); LED in RCP Pro joystick (x1); OLED Display Tile (x7); (x1)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Peripherals	3 channel GPIO (3 opto-isolated inputs / 3 relay outputs)
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	1289 g
Shipping Box Weight	2054 g
In The Box	(This Product) 12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002512

Tekniske tegninger

