

Time Spin

Core Product

SKAARHOJ Time Spin - Universal Instant Replay Controller

Versatile IP-based replay controller designed for use in live production environments. Equipped with the “Blue Pill Inside” technology, it integrates seamlessly with modern replay solutions such as vMix, Softron’s m:Replay, TriCaster 3Play, Neton.Live and DreamChip SSM500. It’s the ultimate solution for creating your own, high quality instant replay systems with software platforms.



Benefits

- Designed for seamless integration with major replay solutions including Softron m:replay and vMix.
- Provides comprehensive replay control for a variety of platforms, including TriCaster and DreamChip SSM500.
- Utilizes the Raw Panel Protocol for versatile compatibility across multiple replay systems.
- Enhances live production quality with precise and responsive replay management.
- Facilitates dynamic and engaging broadcasts with advanced control features.
- Powered by the Blue Pill Inside for reliable performance and extensive functionality.

Features

- Extensive list of supported devices
- Advanced ergonomics
- Versatile connectivity via IP
- Durable all metal construction
- Unique metal dual-layer hall effect jog wheel with clutch
- 10 high quality individually addressable RGB NKK buttons
- In-house designed all-metal T-bar for speed control
- Large Oled screen for referencing settings and button functions
- 8 silicone buttons for selecting clips, macros, replay banks and more
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested - adopted by professionals worldwide

Hardware Specifications	
Component Highlights	Combined Jog/Shuttle Wheel SKAARHOJ Hall Effect T-Bar Sculptured cap NKK broadcast buttons
Buttons	Elastomer Button (x10); Sculptured Hard Cap Button (x10)
Encoders	Jog encoder (x1)
Analog Components	T-bar (x1); Shuttle wheel (x1)
Programmable OLED Tiles	256x64 pixels, gray (x1); 128x32 pixels, gray (x4); 64x32 pixels, gray (x8)
Other	OLED Display (x1); OLED Display Tile (x12)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Peripherals	USB-A 2.0 (500 mA) for Stream Deck, X-keys, additional networking adapters, frame grabbers etc.
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	1126 g
Shipping Box Weight	1968 g
In The Box	(This Product) 12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074003212

Technical Drawings

